

WHEEL LOADER ZL50F



Rated capacity 3m³
Rated weight 5000Kg
Operating weight 16000Kg
Performance of bucket being set level Yes
Static tilting load at full steering position 98KN
Max. breakout force 172.6KN
Max. drawbar pull 151.9KN
Max. grade ability 30°
Total of three time: lifting-dumping-lowering 11.3s
Max.dump height 3098mm
Max.dump reach 1198mm
Min. ground clearance 450mm
Wheel base 3200mm
Overall dimensions (length*width*height) 7836*3010*3300mm

Engine STEYR
Model WDWD12G220E11
Pattern Inline,water cooled, dir.inject, fourstrokes

Cylinder-bore*stroke 6-126*130
Max.torsion 779Nm
Rated power 162KW
Min.fuel consuming rate 214g/kw.h
Specified rotational speed 2200r/min
Model of torque device YJ375
Pattern 3-element,single stage
Number of great shift 4 forward,4 reverse

Max.travel speed 38km/h
Main reducer type Spiral bevel gear, moderation of first stage
Pattern of wheelside moderation Single stage planetary
Tire size 23.5-25
Front type pressure 392KPa
Rear type pressure 343KPa
Pattern Articulated and hydraulic steering, load sensing meets
Steering angle (each direction) 35 C±1
Min.turning radius(outside of bucket) 7268mm
Valve distributing working DF32-2C
Working pumps CBG3100
Brake system Air assisted oil type four wheel brake
Parking brake Air cutting control inner expand hoof
Fuel capacity 320L
Pressure of working hydraulic system 160kfg/cm²

PRICE: USD 47.897,50
FOB CHINA

DELIVERY TIME: SHORT PERIOD